

CALACATTA BLANCO COLLECTION

MODEL: CALACATTA BLANCO MATTE 16X48 (WALL)		
	CODE: HTC500	EDITION: 1
CLASSIFICATION (UNE-EN-14411): Grupo BIII. Anexo L		DECLARATION OF BENEFITS: 05DP
STANDARD	CHARACTERISTICS	TEST RESULT
UNE-EN ISO 10545-3	Water absorption	E > 10%
UNE-EN ISO 10545-4	Breaking strength (N)	1100
UNE-EN ISO 10545-4	Modulus of rupture (N/mm ²)	20
UNE-EN ISO 10545-6	Resistance to deep abrasion (mm ³)	
UNE-EN ISO 10545-7	Abrasion resistance	
	Class ----- Stage	Rev.
UNE-EN ISO 10545-9	Thermal shock resistance	
UNE-EN ISO 10545-11	Resistance to crazing	O.k.
UNE-EN ISO 10545-12	Frost Resistance	
UNE-EN ISO 10545-13	Chemical Resistance	
	Household Chemicals	A
	Swimming pool salts	A
	Citric Acid	IA
	Lactic Acid	
	Hydrochloric Acid low concentrations	IA
	Hydrochloric Acid high concentrations	
	Potassium Hydroxide low concentrations	IA
Potassium Hydroxide high concentrations		
UNE-EN ISO 10545-14	Resistance to staining	
	Fe2O3 / Cr2O3	Class 5
	Iodine / alcohol solution	Class 5
	Light oil	Class 5
UNE-41901:2017 EX	Slip Resistance	
Dimension (mm)	398x1198	Thickness (mm)
		10,9
Classification according to Saloni quality:		

CALACATTA BLANCO COLLECTION

MODEL: CALACATTA FOUNTAIN BLANCO MATTE 16X48			
		CODE: HSF500	EDITION: 1
CLASSIFICATION (UNE-EN-14411): Grupo BIII. Anexo L		DECLARATION OF BENEFITS: 05DP	
STANDARD	CHARACTERISTICS	TEST RESULT	
UNE-EN ISO 10545-3	Water absorption	E > 10%	
UNE-EN ISO 10545-4	Breaking strength (N)	1100	
UNE-EN ISO 10545-4	Modulus of rupture (N/mm ²)	20	
UNE-EN ISO 10545-6	Resistance to deep abrasion (mm ³)		
UNE-EN ISO 10545-7	Abrasion resistance		
	Class		
	Stage	Rev.	
UNE-EN ISO 10545-9	Thermal shock resistance		
UNE-EN ISO 10545-11	Resistance to crazing	O.k.	
UNE-EN ISO 10545-12	Frost Resistance		
UNE-EN ISO 10545-13	Chemical Resistance		
	Household Chemicals	A	
	Swimming pool salts	A	
	Citric Acid	IA	
	Lactic Acid		
	Hydrochloric Acid low concentrations	IA	
	Hydrochloric Acid high concentrations		
	Potassium Hydroxide low concentrations	IA	
Potassium Hydroxide high concentrations			
UNE-EN ISO 10545-14	Resistance to staining		
	Fe2O3 / Cr2O3	Class 5	
	Iodine / alcohol solution	Class 5	
	Light oil	Class 5	
UNE-41901:2017 EX	Slip Resistance		
Dimension (mm)	398x1198	Thickness (mm)	10,9
Classification according to Saloni quality:			

CALACATTA BLANCO COLLECTION

MODEL: CALACATTA BLANCO MATTE 30X30 (FLOOR)		
	CODE: GYE500	EDITION: 1
CLASSIFICATION (UNE-EN-14411): Grupo BIa. Anexo G		DECLARATION OF BENEFITS: 03DP
STANDARD	CHARACTERISTICS	TEST RESULT
UNE-EN ISO 10545-3	Water absorption	E < 0,5%
UNE-EN ISO 10545-4	Breaking strength (N)	2200
UNE-EN ISO 10545-4	Modulus of rupture (N/mm ²)	44
UNE-EN ISO 10545-6	Resistance to deep abrasion (mm ³)	130
UNE-EN ISO 10545-7	Abrasion resistance	
	Class	
	Stage	Rev.
UNE-EN ISO 10545-9	Thermal shock resistance	Ok
UNE-EN ISO 10545-11	Resistance to crazing	O.k.
UNE-EN ISO 10545-12	Frost Resistance	Resist
UNE-EN ISO 10545-13	Chemical Resistance	
	Household Chemicals	A
	Swimming pool salts	A
	Citric Acid	IA
	Lactic Acid	HA
	Hydrochloric Acid low concentrations	IA
	Hydrochloric Acid high concentrations	HA
	Potassium Hydroxide low concentrations	IA
Potassium Hydroxide high concentrations	HA	
UNE-EN ISO 10545-14	Resistance to staining	
	Fe2O3 / Cr2O3	Class 5
	Iodine / alcohol solution	Class 5
	Light oil	Class 5
UNE-41901:2017 EX	Slip Resistance	C1
Dimension (mm)	747x747	Thickness (mm)
Classification according to Saloni quality:		D