

HEIRLOOM COLLECTION

HEIRLOOM SAGE 2.5X10 & HEIRLOOM SAND 2.5X10

Model: **HEIRLOOM SAGE 2.5X10 & HEIRLOOM SAND 2.5X10**
 Reference: **32958 (SAGE) 32956 (SAND)**
 Size: **6X25** cm
 Thickness: **10,00** mm
 Finish: **Natural**
 Body Type: **PORCELAIN - GROUP BIa**
GL - GLAZED Ceramic Tile

Water absorption

EN ISO-10545-3	Water absorption	< 0,5 %
----------------	------------------	---------

Dimensional characteristics

EN ISO-10545-2	Surface quality	> 95%
EN ISO-10545-2	Curvature flatness	± 0,5 % / ± 2,0 mm
EN ISO-10545-2	Thickness	± 5% / ± 0,5 mm
EN ISO-10545-2	Length and Width	± 0,6 % / ± 2,0 mm
EN ISO-10545-2	Rectangularity	± 0,5% / ± 2,0 mm
EN ISO-10545-2	Straightness of sides	± 0,5 % / ± 1,5 mm

Mechanical characteristics

EN ISO 10545-11	Crazing resistance	Pass
EN ISO 10545-12	Frost resistance	Pass
EN ISO 10545-9	Thermal shock resistance	Pass
EN ISO-10545-4	Breaking strength	> 1300 N
EN ISO-10545-4	Modulus of rupture	> 35 N/mm ²

Surface characteristics

EN ISO 10545-7	Visible failure at No of revolutions	-
EN-101	Surface scratch resistance	4

Chemical characteristics

EN ISO-10545-13	High concentrations of acids and alkalis	HA/HA/HA
EN ISO-10545-13	Low concentrations of acids and alkalis	LA/LA/LA
EN ISO-10545-13	Household chemicals and swimming pool salts	A/A
EN ISO-10545-14	Stain resistance	5/-/5/5

CE MARKING



CE Declaration of Performance: 001CPR2017-08-01

TORONTO
 115 Carnarvon Street
 Toronto, ON M6M 3C9
 T 416 413 9008
 F 416 413 9652

TROY
 1700 Stutz Drive, Ste 92 & 94
 Troy, MI 48084
 T 248 643 6520
 F 248 643 6523

Please note, all specifications have been supplied by the manufacturer and are subject to change.

Email: mail@cercantile.com
 Website: www.cercantile.com

HEIRLOOM COLLECTION

HEIRLOOM WHITE, GREY, GREEN & BLUE 2.5X10

Model: **HEIRLOOM WHITE, GREY, GREEN & BLUE 2.5X10**
 Reference: **31034 (WHITE) 31035 (GREY) 31036 (GREEN) 31037 (BLUE)**
 Size: **6X25** cm
 Thickness: **10,00** mm
 Finish: **Natural**
 Body Type: **PORCELAIN - GROUP BIa**
GL - GLAZED Ceramic Tile

Water absorption

EN ISO-10545-3	Water absorption	< 0,5 %
----------------	------------------	---------

Dimensional characteristics

EN ISO-10545-2	Surface quality	> 95%
EN ISO-10545-2	Curvature flatness	± 0,5 % / ± 2,0 mm
EN ISO-10545-2	Thickness	± 5% / ± 0,5 mm
EN ISO-10545-2	Length and Width	± 0,6 % / ± 2,0 mm
EN ISO-10545-2	Rectangularity	± 0,5% / ± 2,0 mm
EN ISO-10545-2	Straightness of sides	± 0,5 % / ± 1,5 mm

Mechanical characteristics

EN ISO 10545-11	Crazing resistance	Pass
EN ISO 10545-12	Frost resistance	Pass
EN ISO 10545-9	Thermal shock resistance	Pass
EN ISO-10545-4	Breaking strength	> 1300 N
EN ISO-10545-4	Modulus of rupture	> 35 N/mm ²

Surface characteristics

EN ISO 10545-7	Visible failure at No of revolutions	-
EN-101	Surface scratch resistance	5

Chemical characteristics

EN ISO-10545-13	High concentrations of acids and alkalis	HA/HA/HA
EN ISO-10545-13	Low concentrations of acids and alkalis	LA/LA/LA
EN ISO-10545-13	Household chemicals and swimming pool salts	A/A
EN ISO-10545-14	Stain resistance	5/-/5/5

Non-slip characteristics

UNE-41901:2017 EX	Slip resistance (pendulum test)	0
-------------------	---------------------------------	---

CE MARKING



CE Declaration of Performance: 001CPR2017-08-01

TORONTO
 115 Carnarvon Street
 Toronto, ON M6M 3C9
 T 416 413 9008
 F 416 413 9652

TROY
 1700 Stutz Drive, Ste 92 & 94
 Troy, MI 48084
 T 248 643 6520
 F 248 643 6523

Please note, all specifications have been supplied by the manufacturer and are subject to change.

Email: mail@cercantile.com
 Website: www.cercantile.com

HEIRLOOM COLLECTION

HEIRLOOM WHITE 6X6 & HEIRLOOM GREY 6X6

Model: **HEIRLOOM WHITE 6X6 & HEIRLOOM GREY 6X6**

Reference: **31039 (WHITE) 31040 (GREY)**

Size: **14,8X14,8** cm

Thickness: **9,00** mm

Finish: **Natural**

Body Type: **PORCELAIN - GROUP BIa**

GL - GLAZED Ceramic Tile

Water absorption

EN ISO-10545-3	Water absorption	< 0,5 %
----------------	------------------	---------

Dimensional characteristics

EN ISO-10545-2	Surface quality	> 95%
EN ISO-10545-2	Curvature flatness	± 0,75 mm
EN ISO-10545-2	Thickness	± 0,5 mm
EN ISO-10545-2	Length and Width	± 0,9 mm
EN ISO-10545-2	Rectangularity	± 0,75 mm
EN ISO-10545-2	Straightness of sides	± 0,75 mm

Mechanical characteristics

EN ISO 10545-11	Crazing resistance	Pass
EN ISO 10545-12	Frost resistance	Pass
EN ISO 10545-9	Thermal shock resistance	Pass
EN ISO-10545-4	Breaking strength	> 1300 N
EN ISO-10545-4	Modulus of rupture	> 35 N/mm ²

Surface characteristics

EN ISO 10545-7	Visible failure at No of revolutions	-
EN-101	Surface scratch resistance	5

Non-slip characteristics

UNE-41901:2017 EX	Slip resistance (pendulum test)	0
-------------------	---------------------------------	---

CE MARKING



CE Declaration of Performance: **001CPR2017-08-01**