

CRISSCROSS COLLECTION

MODEL:	CODE: DTZ513	EDITION: 1
CLASSIFICATION (UNE-EN-14411): Grupo B1a, Anexo G		
DECLARATION OF BENEFITS: 03DP		
STANDARD	CHARACTERISTICS	TEST RESULT
UNE-EN ISO 10545-3	Water absorption	E < 0,5%
UNE-EN ISO 10545-4	Breaking strength (N)	Min. 2000
UNE-EN ISO 10545-4	Modulus of rupture (N/mm ²)	Min. 35
UNE-EN ISO 10545-6	Resistance to deep abrasion (mm ³)	< 175
UNE-EN ISO 10545-7	Abrasion resistance	
	Class	
	Stage	Rev.
UNE-EN ISO 10545-9	Thermal shock resistance	CUMPLE
UNE-EN ISO 10545-11	Resistance to crazing	O.k.
UNE-EN ISO 10545-12	Frost Resistance	Resist
UNE-EN ISO 10545-13	Chemical Resistance	
	Household Chemicals	Min. GB
	Swimming pool salts	Min. GB
	Citric Acid	Min. GLB
	Lactic Acid	Min. GHB
	Hydrochloric Acid low concentrations	Min. GLB
	Hydrochloric Acid high concentrations	Min. GHB
	Potassium Hydroxide low concentrations	Min. GLB
UNE-EN ISO 10545-14	Potassium Hydroxide high concentrations	Min. GHB
	Resistance to staining	
	Fe2O3 / Cr2O3	Class 4
	Iodine / alcohol solution	Class 4
UNE-ENV 12633:2003	Slip Resistance	
Dimension (mm)	450x901	Thickness (mm) 10,4
Classification according to BRAND quality:		



Printing date: 01/02/2018

DECLARACIÓN DE PRESTACIONES (DECLARATION OF PERFORMANCE) Nº. 03DP

- Código de identificación única del producto tipo:
Unique identification code of the product-type:
Baldosa cerámica prensada en seco, con absorción de agua E_b ≤ 0.5%
Dry-pressed ceramic tiles, with water absorption E_b ≤ 0.5%
- Usos previstos:
Entended use/es:
Para suelos y paredes interiores y exteriores
For internal and external floorings and walls
- Sistema de evaluación y verificación de la constancia de prestaciones (EVCP):
System/s of assessment and verification of constancy of performance (AVCP):
Sistema 4
System 4
- Norma armonizada:
Harmonised standard:
EN 14411:2012
- Organismo notificado:
Notified body/ies:
No aplica
Not apply
- Prestaciones declaradas:
Declared performances:

Características esenciales Essential Characteristics	Prestaciones Performance
Reacción al fuego Reaction to fire	A1 _{FL} /A1
Emisión de sustancias peligrosas: Release of dangerous substance, for: Cadmio (Cadmium) Plomo (Lead)	PND PND
Fuerza de rotura Breaking strength	e < 7.5 ≥ 700 N e ≥ 7.5 ≥ 1300 N
Deslizamiento Slipperiness	PND
Propiedades táctiles Tactility	PND
Adhesión, para: Bond strength/adhesion, for: Adhesivo cementoso tipo C2 (Cementitious adhesive, type C2)	> 1 N/mm ²
Durabilidad para: usos interiores Durability for: internal use	Cumple (Pass)
Durabilidad para usos exteriores: resistencia a la helada Durability for external use: freeze-thaw resistance	Cumple (Pass)
Resistencia al choque térmico Thermal shock resistance	Cumple (Pass)

Las prestaciones del producto identificado anteriormente son conformes con el conjunto de prestaciones declaradas. La presente declaración de prestaciones se emite, de conformidad con el Reglamento (UE) nº 305/2011, bajo la sola responsabilidad del fabricante arriba indicado.
The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of conformity is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

TORONTO
115 Carnarvon Street
Toronto, ON M6M 3C9
T 416 413 9008
F 416 413 9652

TROY
1700 Stutz Drive, Ste 92 & 94
Troy, MI 48084
T 248 643 6520
F 248 643 6523

Please note, all specifications have been supplied
by the manufacturer and are subject to change.

Email: mail@cercantile.com
Website: www.cercantile.com